


**Features**

- Stopping plug for unused cable entries
- Stainless Steel
- Thread NPT 1-1/2"
- Without head, installation by means of allen key
- Ex d, Ex e and Ex tb certified
- Suitable for operation in Zone 1, Zone 2, Zone 21 and Zone 22
- Suitable for operation in Class I, Zone 1/2/22
- Suitable for operation in Class I, Division 2 when installed in accordance with NEC501.10(B)(2)
- Degree of protection IP66 / IP68, UL Type 4X
- Packaging unit: 1 piece, kit with accessories

**Assembly****Technical data****Mechanical specifications**

Thread type NPT ANSI ASME B1.20.1

Thread size (TD) NPT 1-1/2"

Degree of protection IP66 / IP68 , UL Type 4X

**Material**

Finish inherent color silver

Stopping plug stainless steel

**Mass**

Individual component approx. 283 g

Packing unit approx. 293 g

**Dimensions**

Diameter thru-hole (DT) 48.3 ... 48.5 mm

Thread length (TL) 25 mm

Total length (L) 25 mm

Key size (KS) 14 mm

**Tightening torque**

Nut torque at enclosure (SW1) 15 Nm

**Ambient conditions**

Ambient temperature -60 ... 130 °C (-76 ... 266 °F)

**Data for application in connection with hazardous areas**

EU-Type Examination Certificate CESI 15ATEX029X

**Marking**


⊕ II 2 GD  
Ex d IIC Gb  
Ex e IIC Gb  
Ex tb IIIC Db

**International approvals**

UL approval

cULus	E305142 tested to UL 50E and UL 508A
CSA approval	CSA C22.2, No. 14-13
IECEX approval	IECEX CES 15.0006X
<b>Conformity</b>	
Degree of protection	EN 60529
<b>General information</b>	
Delivery quantity	1
Scope of delivery	Stopping Plugs, Metal brief instructions
Supplementary information	EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity, Attestation of Conformity and instructions have to be observed where applicable. For information see <a href="http://www.pepperl-fuchs.com">www.pepperl-fuchs.com</a> .

**Dimensions**



**Legend**

1	Stopping plug
KS	Key size
L	Total length
TD	Thread size
TL	Thread length

Release date 2018-09-21 13:51 Date of issue 2018-09-21 291456\_eng.xml

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0002  
pa-info@us.pepperl-fuchs.com

Germany: +49 621 776 2222  
pa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091  
pa-info@sg.pepperl-fuchs.com