
Features

- Sealing element for installation of cable glands in enclosures
- Accessory for CG.NA.* size M40 ... M50S / NPT1-1/4" ... NPT1-1/2S" cable glands metal
- Accessory for CG.EM.* size M50 / NPT1-1/2" cable glands metal
- Polyamide
- Ex e and Ex tb certified
- Suitable for operation in Zone 1, Zone 2, Zone 21 and Zone 22
- Packaging unit: 5 pieces, without accessories

Assembly





Technical data	
Mechanical specifications	
Degree of protection	IP66 / IP68
Material	Polyamide (PA)
Finish	inherent color green
Mass	
Individual component	approx. 9 g
Packing unit	approx. 55 g
Dimensions	
Diameter (D)	27.8 mm
Outer diameter (DO)	40 mm
Length of pin (PL)	24 mm
Total length (L)	34 mm
Ambient conditions	
Ambient temperature	-60 70 °C (-76 158 °F)
Data for application in connection with	
hazardous areas	
EU-Type Examination Certificate	IMQ 14 ATEX 012X
Marking	© II 2 GD
	Ex e IIC Gb Ex tb IIIC Db
International approvals	EX ID IIIC DD
IECEx approval	IECEx IMQ 14.0004X
Conformity	ILOLA IIVIQ 14.0004A
Degree of protection	EN 60529
General information	LIV 00323
Note	For exact reference to types and sizes of cable glands please refer to the specific datasheets
Delivery quantity	5
Donvery quartity	l ▼

Scope of delivery	Sealing Plugs for metal Cable Glands brief instructions (1 copy)
Supplementary information	EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity, Attestation of Conformity and instructions have to be observed where applicable. For information see www.pepperl-fuchs.com.

Dimensions

