


**Features**

- Stopping plug for unused cable entries
- Stainless Steel
- Thread NPT 1-1/2"
- Without head, installation by means of allen key
- Ex d, Ex e and Ex tb certified
- Suitable for operation in Zone 1, Zone 2, Zone 21 and Zone 22
- Suitable for operation in Class I, Zone 1/2/22
- Suitable for operation in Class I, Division 2 when installed in accordance with NEC501.10(B)(2)
- Degree of protection IP66 / IP68, UL Type 4X
- Packaging unit: 5 pieces, without accessories


**Assembly****Technical data****Mechanical specifications**

Thread type	NPT ANSI ASME B1.20.1
Thread size (TD)	NPT 1-1/2"
Degree of protection	IP66 / IP68 , UL Type 4X
Material	
Finish	inherent color silver
Stopping plug	stainless steel
Mass	
Individual component	approx. 283 g
Packing unit	approx. 1.56 kg
Dimensions	
Diameter thru-hole (DT)	48.3 ... 48.5 mm
Thread length (TL)	25 mm
Total length (L)	25 mm
Key size (KS)	14 mm
Tightening torque	
Nut torque at enclosure (SW1)	15 Nm
<b>Ambient conditions</b>	
Ambient temperature	-60 ... 130 °C (-76 ... 266 °F)
<b>Data for application in connection with hazardous areas</b>	
EU-Type Examination Certificate	CESI 15ATEX029X
Marking	⊕ II 2 GD Ex d IIC Gb Ex e IIC Gb Ex tb IIIC Db
<b>International approvals</b>	
UL approval	

**Data for application in connection with hazardous areas****International approvals**

cULus	E305142 tested to UL 50E and UL 508A
CSA approval	CSA C22.2, No. 14-13
IECEX approval	IECEX CES 15.0006X
<b>Conformity</b>	
Degree of protection	EN 60529
<b>General information</b>	
Delivery quantity	5
Scope of delivery	Stopping Plugs, Metal, Hexagon Socket Head brief instructions (1 copy)
Supplementary information	EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity, Attestation of Conformity and instructions have to be observed where applicable. For information see <a href="http://www.pepperl-fuchs.com">www.pepperl-fuchs.com</a> .

**Dimensions**



**Legend**

1	Stopping plug
KS	Key size
L	Total length
TD	Thread size
TL	Thread length

Release date 2018-09-21 13:51 Date of issue 2018-09-21 400873\_eng.xml