

Datasheet - ELDEKWS24



Command and signalling devices / Contact and light terminal blocks (EF/EL) System / Light terminal blocks with integrated multi-LED / Light terminal block ELD

- Cage clamps
- Mounting flange position 3
- white LED
- 24 VAC/DC



(Minor differences between the printed image and the original product may exist!)

Ordering details

Product type description	ELDEKWS24
Article number	101167385
EAN Code	
eCl@ss	27-37-13-02

Global Properties

Permanent light	Leuchtelement ELD
Standards	IEC/EN 60947-1, EN 60947-5-1
Compliance with the Directives (Y/N) 	No
Terminal designations	X1-X2
Mounting position	arbitrarily
Materials	
- Material of the housings	Plastic, glass-fibre reinforced thermoplastic self-extinguishing
Weight	20

Mechanical data

Connection type	Cage clamps, WAGO Cage Clamp
Cable section	
- Min. Cable section	2 x 0,08
- Max. Cable section	2 x 1.5

Mounting flange position	3
mounting	pluggable
terminals	Protection against polarity reversal

Ambient conditions

Ambient temperature	
- Min. environmental temperature	-25
- Max. environmental temperature	+80
Protection class	
- Protection class-Terminals	IP20

Electrical data

Rated insulation voltage Ui	440 V
Rated operating voltage Ue	250 V


LED switching conditions display

With integrated LED (Y/N)	Yes
LED switching conditions display	
- Supply voltage Ub	24 VAC/DC
- colour of the LED	☐ White

Dimensions

Dimensions	
- Width	10 mm
- Depth	51 mm
- Length	46 mm

Diagram





Note Diagram

- positive break NC contact
- active
- no active
- Normally-open contact
- Normally-closed contact

Documents


CCC certification (en) 1 MB, 20.06.2017 Code: q_efelp02	
CCC certification (cn) 1 MB, 20.06.2017 Code: q_efelp03	

Images



Pos.1 Pos.3 Pos.2

Application



Operating principle

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 13.02.2019 - 12:47:52h Kasbase 3.3.0.F.64I