

## Datasheet - RMEFGB

Command and signalling devices / Push buttons and pilot lights - "R" Program / RME - Illuminated signal



- integrated multi-LED, extra bright in device head
- flat dome



(Minor differences between the printed image and the original product may exist!)

### Ordering details

Product type description	RMEFGB
Article number	101188316
EAN Code	
eCl@ss	27-37-12-11

### Approval

Approval



### Global Properties

Permanent light	RME - Illuminated signal
Standards	IEC/EN 60947-1, EN 60947-5-1
Compliance with the Directives (Y/N)	Yes
Suitable for safety functions (Y/N)	No
Mounting	mounting flange
Mounting position	arbitrarily
Materials	
- Material of the dome	Glass
- Material of the front ring	Aluminium
Design	LED - Illuminated signal - Front plate mounting
Form	round, flat dome

Color	
- Colour of the dome	<span style="color: yellow;">■</span> yellow
- Colour of the front ring	<span style="color: gray;">■</span> Silver
Weight	55
Can be illuminated (Y/N)	Yes

### Mechanical data

---

mounting flange available (Y/N)	Yes
Front plate thickness	
- min. front plate thickness	1
- max. front plate thickness	6
Tightening torque for fixing screws	2

### Ambient conditions

---

Ambient temperature	
- Min. environmental temperature	-25
- Max. environmental temperature	+75
Storage and transport temperature	
- Min. Storage and transport temperature	-
- Max. Storage and transport temperature	-
Fully insulated (Y/N)	Yes
Sealing type	membrane, lip seal, Form seals
Protection class	IP65

### LED switching conditions display

---

With integrated LED (Y/N)	Yes
- for 24	

### Dimensions

---

Dimensions	
- Height	
- Diameter total	39.5
Height of the dome	0,5
Diameter of the front ring	39.5
Diameter of the dome	25
Hole, diameter	22.3 + 0,4
Spacing	40 x 60

### Included in delivery

---

Mounting flange RLM (1188815) is included in delivery

### Documents

---

**Operating instructions and Declaration of conformity (it)** 2 MB, 14.06.2017

Code: mrl\_programme-e-n-r\_it

**Operating instructions and Declaration of conformity (en)** 1 MB, 06.11.2018

Code: mrl\_programme-e-n-r\_en

**Operating instructions and Declaration of conformity** (pl) 2 MB, 12.10.2017

Code: mrl\_programme-e-n-r\_pl

**Operating instructions and Declaration of conformity** (jp) 2 MB, 28.06.2017

Code: mrl\_programme-e-n-r\_jp

**Operating instructions and Declaration of conformity** (pt) 2 MB, 31.05.2017

Code: mrl\_programme-e-n-r\_pt

**Operating instructions and Declaration of conformity** (de) 1 MB, 06.11.2018

Code: mrl\_programme-e-n-r\_de

**Operating instructions and Declaration of conformity** (es) 1 MB, 05.12.2018

Code: mrl\_programme-e-n-r\_es

**Operating instructions and Declaration of conformity** (nl) 1 MB, 05.12.2018

Code: mrl\_programme-e-n-r\_nl

**Operating instructions and Declaration of conformity** (fr) 1 MB, 05.12.2018

Code: mrl\_programme-e-n-r\_fr

**Operating instructions and Declaration of conformity** (cn) 2 MB, 21.06.2017

Code: mrl\_programme-e-n-r\_cn

## Images

---

## System components

---

### Light terminal block



#### Light terminal block RL

- Print with incandescent lamp symbol

### spare part



#### mounting flange (R)

---

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 13.02.2019 - 12:56:33h Kasbase 3.3.0.F.64I