## **Datasheet - EDMWS**



Command and signalling devices / Push buttons and pilot lights - "E" Program / ED - Push button



- with membrane
- Symbols still clearly visible under transparent membrane

(Minor differences between the printed image and the original product may exist!)

## **Ordering details**

Product type description EDMWS
Article number 101006272
EAN Code

eCl@ss 27-37-12-12

### **Approval**

Approval

Form



Round

#### **Global Properties**

Permanent light ED - Push button

Standards IEC/EN 60947-1, EN 60947-5-1

Compliance with the Directives (Y/N)

No

Suitable for safety functions (Y/N) No
Mounting mounting flange

Mounting position arbitrarily Materials

- Material of the operators- Material of the front ringAluminium

Design Embeddable button - Front plate mounting

#### Color White - Colour of the operating element Silver - Colour of the front ring Weight 35 Can be illuminated (Y/N) No With membrane (Y/N) Yes inflated edge (Y/N) No **Mechanical data** 10.000.000 operations Mechanical life Switching frequency 1000 2 Actuating force Actuating stroke 4 Latching (Y/N) Nο without Unlocking type Probing possible (Y/N) Yes notice Unlocking by rotating the knurled button clockwise mounting flange available (Y/N) Yes Front plate thickness - min. front plate thickness - max. front plate thickness 6 Tightening torque for fixing screws 0,6 **Ambient conditions** Ambient temperature -25 - Min. environmental temperature - Max. environmental temperature +80 Storage and transport temperature - Min. Storage and transport temperature - Max. Storage and transport temperature Fully insulated (Y/N) Yes Sealing type membrane, lip seal, Form seals Protection type IP IP65 LED switching conditions display With integrated LED (Y/N) No **Dimensions** Dimensions - Height 14 - Diameter total 29.5 - Diameter of the front ring Ø 29.5 - Diameter of touch surface 23 Hole, diameter 22.3 + 0.4Mounting hole 22 40 x 50 Spacing notice

# **Images**

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal The data and values have been checked throroughly. Technical modifications and errors excepted. Generiert am 13.02.2019 - 12:48:12h Kasbase 3.3.0.F.64I