

## Datasheet - ESTS32S1

Command and signalling devices / Push buttons and pilot lights - "E" Program /  
ESS/EST-Key-Selector switch



(Minor differences between the printed image and the original product may exist!)

### Ordering details

Product type description	ESTS32S1
Article number	101006396
EAN Code	
eCl@ss	27-37-12-13

### Approval

Approval



### Global Properties

Permanent light	EST - Schlüssel Wahltaster
Standards	IEC/EN 60947-1, EN 60947-5-1
Compliance with the Directives (Y/N)	
Suitable for safety functions (Y/N)	No
Mounting	mounting flange
Mounting position	arbitrarily
Materials	
- Material of the front ring	Aluminium
- Material of the cylinder lock	Steel
Design	Key - Selector switch - Front plate mounting
Form	
Color	
- Colour of the front ring	■ Silver
- Colour of the cylinder lock	■ Silver
Weight	90
Can be illuminated (Y/N)	No
Closure	EKM30

### Mechanical data

Mechanical life	300.000 operations
Number of the touch position	3

Latching (Y/N)	No
Unlocking type	Rotating unlatcher
Probing possible (Y/N)	Yes
Touch position	right
Latching position	left
switching angle	right 35 / left 55
Number of plunger	2
Key withdrawal position	Position I
Number of switch positions	
Front plate thickness	
- min. front plate thickness	1
- max. front plate thickness	6
Tightening torque for fixing screws	0,6

## Ambient conditions

---

Ambient temperature	
- Min. environmental temperature	0
- Max. environmental temperature	+80
Storage and transport temperature	
- Min. Storage and transport temperature	-
- Max. Storage and transport temperature	-
Fully insulated (Y/N)	Yes
Sealing type	membrane, lip seal, Form seals
Protection type IP	IP65

## LED switching conditions display

---

With integrated LED (Y/N)	No
---------------------------	----

## Dimensions

---

Dimensions	
- Height with key	60
- Diameter of the front ring	Ø 29.5
- diameters for the cylinder lock	Ø 22 mm mm
- Hole, diameter	22.3 + 0,4
Spacing	40 x 50

## notice

---

notice	Special closure on request
--------	----------------------------

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 13.02.2019 - 12:48:32h Kasbase 3.3.0.F.64I