

## Datasheet - ZF 232-11

Foot switch / F 232

☒ Preferred typ



- 2 Contacts
- Metal enclosure
- single-pedal types
- High level of stability
- Cable entry M 20 x 1.5
- Low operating height of pedal
- Also available as safety foot switch

(Minor differences between the printed image and the original product may exist!)

### Ordering details

Product type description	ZF 232-11
Article number	101181537
EAN Code	4030661326252
eCl@ss	27-37-12-18

### Approval

Approval



### Global Properties

Permanent light	F 232
Standards	EN 60947-5-1, DIN VDE 0660-200, BG-GS-ET-15
Compliance with the Directives (Y/N)	Yes
Suitable for safety functions (Y/N)	No
Materials	
- Material of the housings	Aluminium
- Material of the cover	Aluminium
- Material of the protective shield	Aluminium
- Material of the pedal	Plastic, glass-fibre reinforced thermoplastic
Housing coating	powder-coated
Colouring	
- Enclosure color	RAL 9006 (White aluminum)
Weight	1030
Suitable for EMERGENCY-OFF (Y/N)	No

Protection hood (Y/N)	No
-----------------------	----

Mechanical data

Design of electrical connection	Screw connection
Cable section	
- Min. Cable section	
- Max. Cable section	1 x 2.5
Mechanical life	> 1.000.000 operations
notice	All indications about the cable section are including the conductor ferrules.
Latching (Y/N)	No
Probing possible (Y/N)	Yes

Ambient conditions

Ambient temperature	
- Min. environmental temperature	-25
- Max. environmental temperature	+70
Protection type IP	IP65 to IEC/EN 60529

Electrical data

Design of control element	Normally open contact (NO), Opener (NC)
Switching principle	Snap action
Number of shutters	1
Number of openers	1
Rated impulse withstand voltage U <sub>imp</sub>	6 kV
Rated insulation voltage U <sub>i</sub>	500 V
Thermal test current I <sub>the</sub>	10 A
Utilisation category	AC-15: 230 V / 4 A, DC-13: 24 V / 1 A
Max. fuse rating	6 A gG D-fuse

Dimensions

Dimensions	
- Width	170 mm
- Height	189 mm
- Depth	274 mm

Diagram



- Note Diagram
- positive break NC contact
  - active
  - no active
  - Normally-open contact
  - Normally-closed contact

Ordering code

---

(1)F(2) 232-(3)-(4)

(1)

T Slow action

Z Snap action

(2)

without without Protective shield

H with Protective shield

(3)

11 1 Normally open contact (NO) / 1 Opener (NC)

02 2 Opener (NC)

20 2 Normally open contact (NO)

22 2 Normally open contact (NO) / 2 Opener (NC)

04 4 Opener (NC)

40 4 Normally open contact (NO)

(4)

HD 3-phase actuation with pressure point

F with start/stop function

## Documents

---

**Operating instructions and Declaration of conformity** (da) 259 kB, 07.08.2012

Code: mrl\_f232\_da

**Operating instructions and Declaration of conformity** (it) 736 kB, 04.08.2010

Code: mrl\_f232\_it

**Operating instructions and Declaration of conformity** (jp) 925 kB, 16.12.2010

Code: mrl\_f232\_jp

**Operating instructions and Declaration of conformity** (pl) 278 kB, 01.08.2014

Code: mrl\_f232\_pl

**Operating instructions and Declaration of conformity** (fr) 734 kB, 04.08.2010

Code: mrl\_f232\_fr

**Operating instructions and Declaration of conformity** (cs) 260 kB, 12.03.2012

Code: mrl\_f232\_cs

**Operating instructions and Declaration of conformity** (nl) 740 kB, 04.08.2010

Code: mrl\_f232\_nl

**Operating instructions and Declaration of conformity** (pt) 273 kB, 05.01.2015

Code: mrl\_f232\_pt

**Operating instructions and Declaration of conformity** (en) 319 kB, 15.12.2016

Code: mrl\_f232\_en

**Operating instructions and Declaration of conformity** (en) 488 kB, 11.05.2010

Code: mrl\_f232\_en

**Operating instructions and Declaration of conformity** (de) 324 kB, 15.12.2016

Code: mrl\_f232\_de

**Operating instructions and Declaration of conformity** (es) 728 kB, 04.08.2010

Code: mrl\_f232\_es

**CCC certification** (en) 975 kB, 24.05.2016


Code: q\_455p02

**CCC certification** (cn) 948 kB, 24.05.2016

Code: q\_455p03


## Images

---




Dimensional drawing (basic component)

---



Dimensional drawing (basic component)

---



Dimensional drawing (basic component)