Datasheet - MBGAC466

Command and signalling devices / Assembly housing MBGAC / MBGAC





- Emergency stop enclosure with yellow cover in accordance with the ANSI standard
- Emergency stop enclosure with protective collar
- · tailored to robust command devices

(Minor differences between the printed image and the original product may exist!)

Ordering details

Product type description	MBGAC466	
Article number	101213386	
EAN Code		
eCl@ss	27-37-12-05	

No

Approval

Approval

Global Properties

Permanent light

Number of command positions
6

Materials
- Material of the housings

Colouring
- Housing color of upper part

MBGAC - Aufbaugehäuse
6

Aluminium

RAL 7001 ■ Grey

- Housing color of upper part

- color of base part

RAL 7001 ■ Grey

Weight

Protective collar in housing cover (Y/N)

Number of through-holes for the cable gland

Mechanical data

Knockout holes for cable gland (Y/N)	No	
Position of the cable gland	at the front	
Ambient conditions		
Ambient temperature		
- Min. environmental temperature	-25	
- Max. environmental temperature	+80	
Protection class	IP65	
Dimensions		
Dimensions		
- Width	100	
- Height	80	
- Depth	305	
Images		

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal The data and values have been checked throroughly. Technical modifications and errors excepted. Generiert am 13.02.2019 - 12:46:42h Kasbase 3.3.0.F.64l