

Datasheet - CSS-Y-A-8P-VA

Accessories SD interface / SD junction boxes M12



- Accessories for series-wiring with serial diagnostics
- The connector supplies the safety channels with operating voltage.



(Minor differences between the printed image and the original product may exist!)

Ordering details

Product type description	CSS-Y-A-8P-VA
Article number	103008718
EAN Code	
eCl@ss	27-27-24-91

Global Properties

Permanent light	Abschlussstecker für Y-Adapter
Connector	1 x Connector, 8-pole
Design	straight
Weight	20
Recommended combinations	Solenoid interlock, Sensors
notice	Leads the SD interface back to the control cabinet to connect further SD participants of other safety circuits.
	For the wiring, M12 cable extensions can be used. The voltage drop (due to the cable length, cable section, voltage drop per sensor) should be taken into account, as it reduces the maximum number of safety sensors and interlocks with SD interface that can be wired in series.

Mechanical data

termination	M12
Bolting device	Screw locking Stainless steel (VA)

Ambient conditions

Ambient temperature

- Min. environmental temperature	-25
- Max. environmental temperature	+75

Electrical data

Rated operating voltage	30
Operating current	4 A
Fuse rating for the operating voltage	4 A


Dimensions

Dimensions






- Width	16.5
- Height	16.5
- Length	43

Diagram

CSS-Y-A-8P



Note Diagram

-  positive break NC contact
-  active
-  no active
-  Normally-open contact
-  Normally-closed contact

Images

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 13.02.2019 - 12:38:47h Kasbase 3.3.0.F.64I