

Datasheet - SET SL 300-0340

Safety-related tactile sensor / Safety flaps / SL 300



(Minor differences between the printed image and the original product may exist!)

- Robust design
- 2 Contacts
- Can be mounted on existing glue-spreading machines, veneering presses, etc.
- Various lengths available

Ordering details

Product type description	SET SL 300-0340
Article number	101164845
EAN Code	4030661293332
notice	The position switch with safety function is not included in delivery. The following alternatives are available: 1 Normally open contact (NO) / 1 Opener (NC) T3K 335-11Z-U90 - Metal enclosure T3K 336-11Z-U90 - Thermoplastic enclosure
eCl@ss	

Global Properties

Permanent light	SL 300
Standards	EN 60947-5-1
Materials	
- Material of the profile strip	Aluminium
- Material of the side plates	Aluminium
- Material of the latching	Plastic, thermoplastic
Weight	

Ambient conditions

Ambient temperature	
- Min. environmental temperature	-20
- Max. environmental temperature	+55
Storage and transport temperature	
- Min. Storage and transport temperature	-20
- Max. Storage and transport temperature	+70

Protection class	IP67 to IEC/EN 60529
------------------	----------------------

Electrical data

Design of control element	see switch description
Switching principle	see switch description

Dimensions

Dimensions	
- Width	100 mm
- Height	260 mm
- Length (L1)	340 mm

Included in delivery

Supporting profile	
Flap profile	
Latching	
Side plates	
Mounting accessories	

Keywords

Keywords	Safety flaps T3K 335-11Z-U90 T3K 336-11Z-U90
----------	--


Indication legend

1	Supporting profile
2	Flap profile
3	Groove
4	Washer
5	Latching
6	Pin Ø 5 mm
7	Position switches with safety function (T3K 335-11Z-U90, T3K 336-11Z-U90)
L1	Length Aluminium profile section

Documents

Mounting and wiring instructions (de, en, fr) 48 kB, 30.01.2018
Code: m_l30p01

Images



Product

