

Datasheet - BN 65-10Z/1V

Magnetic reed switch / BN 65



(Minor differences between the printed image and the original product may exist!)

- With pre-wired cable
- Non-contact principle
- Long life
- Actuation from front
- Actuating surface and direction of actuation marked by switch symbol
- without bias magnet
- Construction form Ø 13 mm
- Thermoplastic enclosure
- Actuating distance up to 60 mm depending on actuating magnet and version
- with central mounting

Ordering details


Product type description	BN 65-10Z/1V
Article number	101057096
EAN Code	
eCl@ss	27-27-01-04

Approval

Approval



Global Properties

Permanent light	BN 65
Standards	-
Compliance with the Directives (Y/N) 	Yes
suitable for elevators (Y/N)	No
Mounting	central with threaded flange
Active principle	Magnetic drive
Materials	
- Material of the housings	Plastic, glass-fibre reinforced thermoplastic
- Material of the cable mantle	H03VV-F
Housing construction form	cylinder smooth
Weight	70
Recommended actuator	BP 10S, 2 x BP 10S, BP 15S, BP 34S, BP 20S, BP 31S, BP 11S, 2 x BP 11S, BP 12S, 2 x BP 12S, BP 21S, 2 x BP 21S, BP 22S, 2 x BP 22S, BE

Mechanical data

Design of electrical connection	Cable
Cable length	1
Conductors	2 x 0,75
AWG-Number	18
Mechanical life	1.000.000.000 operations
Electrical lifetime	1.000.000 ... 1.000.000.000 operations
Switching frequency	300/
Actuating planes	front side
Active area	front side
Switch distance	5 ... 55 BP 10S = 5 mm 2 x BP 10S = 10 mm BP 15S = 6 mm BP 34S = 20 mm BP 20S = 15 mm BP 31S = 15 mm BP 11S = 5 mm 2 x BP 11S = 15 mm BP 12S = 10 mm 2 x BP 12S = 25 mm BP 21S = 30 mm 2 x BP 21S = 20 ... 55 mm BP 22S = 25 mm 2 x BP 22S = 15 ... 55 mm BE 20S = 6 mm
notice	Actuating distance up to 55 mm depending on actuating magnet and version
Type of actuation	Magnet
resistance to shock	30 g, on sine wave oscillation
resistant to vibration	30 g, on sine wave oscillation
Resistance to vibration	10 ... 55 HZ, Amplitude 1 mm
Bounce duration	0,3 ... 0,6
Latching (Y/N)	No
bias magnet (Y/N)	No
Tightening torque for nuts	22 300
Actuating speed	18
Switching point accuracy	± 0,25 mm

Ambient conditions

Ambient temperature	
- Min. environmental temperature	-25
- Max. environmental temperature	+75
Protection class	IP67

Electrical data

Design of control element	Normally open contact (NO)
Number of shutters	1
Number of openers	0
Switching time - Close	0,3 - 1,5
Switching time - Open	-
Dielectric strength	> 600 (50)
Switching voltage	250

Switching current	3 A
Switching capacity	120 /

Outputs

Design of control output	Reed kontakts
--------------------------	---------------

LED switching conditions display

LED switching conditions display (Y/N)	No
----------------------------------------	----

ATEX

Explosion protection categories for gases	None
Explosion protected category for dusts	None

Dimensions

Dimensions of the sensor	
- Length of sensor	103
- Diameter of sensor	13


notice

The opening and closing functions depend on the direction of actuation, the actuating magnets and the polarity of the actuating magnets. When the switches and actuators come together, the colours must coincide: Red (S) to red (S) and green (N) to green (N). This does not apply to the bistable contact.






Included in delivery

Actuators must be ordered separately.

Diagram



Note Diagram

-  positive break NC contact
-  active
-  no active
-  Normally-open contact
-  Normally-closed contact

Documents

Declaration of conformity (en) 186 kB, 12.07.2018

Code: __bn_p01_en

Declaration of conformity (de) 102 kB, 08.06.2016

Code: __bn_p01

notice - Switch distance (de) 36 kB, 07.08.2009

Code: s_bnbsp01

notice - Switch distance (nl) 39 kB, 07.08.2009

Code: s_bnbsp04

notice - Switch distance (fr) 41 kB, 07.08.2009

Code: s_bnbsp03

notice - Switch distance (pt) 39 kB, 07.08.2009

Code: s_bnbsp10


notice - Switch distance (it) 40 kB, 07.08.2009

Code: s_bnbsp05


notice - Switch distance (es) 38 kB, 07.08.2009

Code: s_bnbsp09

Images




Dimensional drawing (basic component)



Characteristic curve


System components

Actuator




101057432 - BP 22 N (S)

- -metal housing
- S-pole marked red
- N-pole marked green
- Suitable for mounting on ferrous material
- Can be used as N or S magnet




101057534 - BP 21 S

- -metal housing
- S-pole marked red
- Suitable for mounting on ferrous material




101057536 - BP 21 N

- -metal housing
- N-pole marked green
- Suitable for mounting on ferrous material



101059921 - BP 21

- -metal housing
- S-pole marked red
- N-pole marked green
- Suitable for mounting on ferrous material




101059917 - BP 12 N

- -metal housing
- N-pole marked green
- Suitable for mounting on ferrous material




101059916 - BP 12

- -metal housing
- S-pole marked red
- N-pole marked green
- Suitable for mounting on ferrous material




101057533 - BP 11 S

- -metal housing
 - S-pole marked red
 - Suitable for mounting on ferrous material
-




101059923 - BP 11 N

- -metal housing
 - N-pole marked green
 - Suitable for mounting on ferrous material
-




101059922 - BP 11

- -metal housing
 - S-pole marked red
 - N-pole marked green
 - Suitable for mounting on ferrous material
-




101057521 - BP 31 S

- thermoplastic enclosure
 - S-pole marked red
 - Suitable for mounting on ferrous material with a distance of 20 mm
-




101057520 - BP 31 N

- thermoplastic enclosure
 - N-pole marked green
 - Suitable for mounting on ferrous material with a distance of 20 mm
-




101057530 - BP 31

- thermoplastic enclosure
 - S-pole marked red
 - N-pole marked green
 - Suitable for mounting on ferrous material with a distance of 20 mm
-




101057541 - BP 20 S

- -metal housing
 - S-pole marked red
 - Suitable for mounting on ferrous material with a distance of 20 mm
-




101057538 - BP 20 N

- -metal housing
 - N-pole marked green
 - Suitable for mounting on ferrous material with a distance of 20 mm
-



101057549 - BP 20

- -metal housing
- S-pole marked red
- N-pole marked green
- Suitable for mounting on ferrous material with a distance of 20 mm



101057553 - BP 34

- thermoplastic enclosure
- S-pole marked red
- N-pole marked green
- Suitable for mounting on ferrous material with a distance of 25 mm



101060163 - BP 15

- thermoplastic enclosure
- N-pole marked green
- S-pole marked red
- Suitable for mounting on ferrous material with a distance of 18 mm



101057531 - BP 10

- Unenclosed
- Colour coding of poles by labels

K.A. Schmersal GmbH & Co. KG, Mödinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 13.02.2019 - 13:12:14h Kasbase 3.3.0.F.64I