

Datasheet - AZM190-B3/2X15

Solenoid interlock / AZM190 / Actuator



- For very small actuating radii in line with or at 90° to the plane of the actuator

(Minor differences between the printed image and the original product may exist!)

Ordering details

Product type description	AZM190-B3/2X15
Article number	101029938
EAN Code	4030661451695
<i>Replaced article number 101144773</i>	
eCl@ss	27-27-92-16

Global Properties

Permanent light	Beweglicher Betätiger AZM190-B3/2X15
Weight	80

Mechanical data

Design of actuators	flexible
Play key in interlocked condition	approx. 5 mm
Minimum actuating radius	350 mm

notice

The axis of the hinge should be 20 mm above the top edge of the safety switch and in the same plane

On hinged guards, minimum actuating radius at 90° to the plane of the actuator 350 mm

minimum actuating radius on hinged guards in line with the plane of the actuator 350 mm

Documents

Operating instructions and Declaration of conformity (fr) 193 kB, 14.04.2014

Code: mrl_azm190-betaetiger_fr

Operating instructions and Declaration of conformity (es) 193 kB, 08.08.2014

Code: mrl_azm190-betaetiger_es

Operating instructions and Declaration of conformity (en) 179 kB, 21.03.2014

Code: mrl_azm190-betaetiger_en

Operating instructions and Declaration of conformity (nl) 191 kB, 14.04.2014

Code: mrl_azm190-betaetiger_nl

Operating instructions and Declaration of conformity (jp) 241 kB, 14.04.2014

Code: mrl_azm190-betaetiger_jp

Operating instructions and Declaration of conformity (it) 192 kB, 14.04.2014

Code: mrl_azm190-betaetiger_it

Operating instructions and Declaration of conformity (de) 181 kB, 21.03.2014

Code: mrl_azm190-betaetiger_de

Operating instructions and Declaration of conformity (pl) 229 kB, 14.04.2014

Code: mrl_azm190-betaetiger_pl

Images

