

Datasheet - SLC445-ER-0170-30-01

Safety light curtains, Safety light grids / Safety light curtains / SLC445



- Safety type 4 in accordance with IEC 61496-1
- User-friendly parameter setting, no tools required
- Process safety with highest availability
- Integrated set-up tool
- Multifunctional

(Minor differences between the printed image and the original product may exist!)

Ordering details

Product type description	SLC445-ER-0170-30-01
Article number	103005403
EAN Code	
eCl@ss	27-27-27-04

Approval


Approval



Classification

Standards	EN ISO 13849-1, EN 62061
PL	up e
Control category	up 4
PFH value	5.14 x 10 ⁻⁹ /
SIL	up 3
Mission time	20 Years

Global Properties

Permanent light	SLC445 Sicherheits-Lichtvorhang
Standards	EN 61496-1; CLC/TS 61496-2
Compliance with the Directives (Y/N) 	Yes
Operating resource protection class	Protection class 3
Safety type in accordance with IEC 61496-1	4
Materials	
- Material of the housings	Aluminium
Weight	400
Beam coding (Y/N)	Yes
Protection field height	170
Range of the protection field	300 - 10.000
Reaction time	10
Wave length of the sensors	880
Fade-out is possible (Y/N)	Yes
Override possible (Y/N)	Yes
reduced resolution (Y/N)	Yes
Clock control possible (Y/N)	Yes
Muting possible (Y/N)	Yes
Restart block (Y/N)	Yes
Master/slave function	No
Cascadable (Y/N)	No
Monitoring function of downstream devices (Y/N)	Yes
Recommended safety-monitoring module	Series SRB 301

Mechanical data

Detection ability for test bodies	30
Number of beams	8
Design of electrical connection	Connector
- Wiring of the transmitter	connector plug M12, 4-pole
- Wiring of the receiver	connector plug M12, 12-pole
Cable length	100

Ambient conditions

Ambient temperature	
- Min. environmental temperature	-25
- Max. environmental temperature	+50
Storage and transport temperature	
- Min. Storage and transport temperature	-25
- Max. Storage and transport temperature	+70
Protection class	IP67 to IEC/EN 60529

Electrical data

Design of output switching element OSSD	PNP
Power consumption	
- Power consumption Transmitter	< 5
- Power consumption Receiver	< 10
Voltage type	DC
Switching voltage of the OSSD in high state	24 ± 10
Integrated contactor control (Y/N)	Yes

Outputs

Max. output current at secured output 250

Electrical data - Safety outputs

Number of secure semi-conductor outputs 2

Number of secure outputs with contact 0

LED switching conditions display

LED switching conditions display (Y/N) Yes

- Status and diagnostics Yes

- 7-segment display Yes

ATEX

Explosion protection categories for gases None

Explosion protected category for dusts None

Dimensions

Dimensions of the sensor

- Width of sensor 27.8

- Height of sensor Transmitter: 251 / Receiver: 261

- Length of sensor 33

notice

In case of failure (interruption of the 0 V supply) the maximum leakage current is 1 mA.

Included in delivery

Delivery scope of disposable system Transmitter + receiver, Mounting angle

Indication legend

A: total length (Protection field height + 81 mm)

Ordering code

SLC445-E/R(1)-(2)-01

(1)

0170 Protection field height 170 mm

0250 Protection field height 250 mm

0330 Protection field height 330 mm

0410 Protection field height 410 mm

0490 Protection field height 490 mm

0570 Protection field height 570 mm

0650 Protection field height 650 mm

0730 Protection field height 730 mm

0810 Protection field height 810 mm

0890	Protection field height 890 mm
0970	Protection field height 970 mm
1050	Protection field height 1050 mm
1130	Protection field height 1130 mm
1210	Protection field height 1210 mm
1290	Protection field height 1290 mm (<i>Only for Resolution 30 mm, 50 mm</i>)
1370	Protection field height 1370 mm (<i>Only for Resolution 30 mm, 50 mm</i>)
1450	Protection field height 1450 mm (<i>Only for Resolution 30 mm, 50 mm</i>)
1530	Protection field height 1530 mm (<i>Only for Resolution 30 mm, 50 mm</i>)
1610	Protection field height 1610 mm (<i>Only for Resolution 30 mm, 50 mm</i>)
1690	Protection field height 1690 mm (<i>Only for Resolution 30 mm, 50 mm</i>)
1770	Protection field height 1770 mm (<i>Only for Resolution 30 mm, 50 mm</i>)
(2)	
14	Resolution 14 mm, Range 0,3 m ... 7 m
30	Resolution 30 mm, Range 0,3 m ... 10 m

Documents

Operating instructions and Declaration of conformity (jp) 1 MB, 16.07.2014

Code: mrl_slc-slg445_jp

Operating instructions and Declaration of conformity (en) 1 MB, 13.09.2017

Code: mrl_slc-slg445_en

Operating instructions and Declaration of conformity (pt) 1 MB, 19.10.2017

Code: mrl_slc-slg445_pt

Operating instructions and Declaration of conformity (nl) 1 MB, 02.07.2018

Code: mrl_slc-slg445_nl

Operating instructions and Declaration of conformity (pl) 1 MB, 19.01.2018

Code: mrl_slc-slg445_pl

Operating instructions and Declaration of conformity (de) 1 MB, 13.09.2017

Code: mrl_slc-slg445_de

Operating instructions and Declaration of conformity (fr) 1 MB, 18.10.2017

Code: mrl_slc-slg445_fr

Operating instructions and Declaration of conformity (es) 1 MB, 17.10.2017

Code: mrl_slc-slg445_es

Operating instructions and Declaration of conformity (it) 1 MB, 18.10.2017

Code: mrl_slc-slg445_it

BG-test certificate (de, en) 853 kB, 28.05.2014

Code: z_slcp05

Brochure (it) 2 MB, 01.03.2018

Code: b_optoshort_it

Brochure (pt) 2 MB, 26.10.2018

Code: b_optoshort_pt

Brochure (es) 2 MB, 23.10.2018

Code: b_optoshort_es

Brochure (fr) 2 MB, 20.11.2018

Code: b_optoshort_fr

Brochure (en) 2 MB, 23.10.2018

Code: b_optoshort_en

Brochure (pl) 2 MB, 03.08.2018

Code: b_optoshort_pl

Brochure (de) 2 MB, 22.10.2018

Code: b_optoshort_de

EAC certification (ru) 772 kB, 05.10.2015

Code: q_6395p17_ru

EAC certification (ru) 1 MB, 15.03.2018

Code: q_slbp01

Images

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 13.02.2019 - 14:21:14h Kasbase 3.3.0.F.64l