

## Datasheet - LTBU

Control panels / Illuminated pushbutton / Illuminated pushbutton / LT



- **Illuminated signal**
- with concave button
- Touch surface 19 x 19
- Lamp replacement at the front
- 5 different colours available

(Minor differences between the printed image and the original product may exist!)

### Ordering details

Product type description	LTBU
Article number	LTBU
EAN Code	
notice	<b>Can only be ordered in conjunction with the "BDF" operating panel</b>
eCl@ss	

### Global Properties

Permanent light	Leuchttaster LT
Materials	
- Material of the contacts	Ag-Ni 10, 0,2 µm gold flashed
- Material of the operators	Plastic
Color	
- Colour of the operating element	■ Blue
Position control panel	Position 1, 2, 3, 4

### Mechanical data

Mechanical life	1.000.000 operations
Switching frequency	1200
Actuating force	8 N
Actuating stroke	3
resistance to shock	100 g / 6 ms
resistant to vibration	20 g, 10 ... 200 HZ

Bounce duration	< 2 ms at 100 mm/s Actuating speed
Positive break force	1 / Contact

## Ambient conditions

---

Protection class	
- Switching element protection class	IP65

## Electrical data

---

Rated insulation voltage $U_i$	60 V
Rated operating voltage $U_e$	
- Max. Rated operating voltage	24
Thermal test current $I_{the}$	2.5 A
Max. fuse rating	2.5 A
Switching of low voltages	1 mA / 5 V

## Outputs

---

Utilisation category	AC-15: 24 V / 2 A; DC-13: 24 V / 1 A
----------------------	---

## Images

---

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 13.02.2019 - 12:58:27h Kasbase 3.3.0.F.64I