

Datasheet - V-SK4P-M12-S-G-2,0M-BK-2-X-A-4

Connector / Connector M12 / V-SK4M12



- Interconnector
- 4-pole

(Minor differences between the printed image and the original product may exist!)

Ordering details

Product type description	V-SK4P-M12-S-G-2,0M-BK-2-X-A-4
Article number	103002573
EAN Code	
eCl@ss	

Approval

Approval



Global Properties

Permanent light	Verbindungsleitung V-SK4M12
Versions	Interconnector
Materials	
- Material of the housings	Plastic
- Material of the cable mantle	PUR
Connector	male connector - female connector
Design	straight
Colouring	
- Enclosure color	Black
- Cable colour	Black
Cable type	LiF9YH-11YH

Weight	
Coding	A

Mechanical data

termination	M12
Bolting device	Screw locking
Cable length	2
Conductors	4 x 0,34

Ambient conditions

Protection class	IP67
------------------	------


Electrical data

Number of poles	4
Number of cores	4
Rated operating voltage	250
Operating current	4 A






LED switching conditions display

LED switching conditions display (Y/N)	No
--	----


Diagram



Note Diagram

-  positive break NC contact
-  active
-  no active
-  Normally-open contact
-  Normally-closed contact

Images



Contact arrangement

The data and values have been checked thoroughly. Technical modifications and errors excepted.
Generiert am 13.02.2019 - 12:58:08h Kasbase 3.3.0.F.64I