

## Datasheet - PH-COM4-ER-02

Safety light curtains, Safety light grids / Accessories / protective enclosure for Safety light grids and curtains / PH-COM4-ER-xx



(Minor differences between the printed image and the original product may exist!)

### Ordering details

Product type description	PH-COM4-ER-02
Article number	103026841
EAN Code	
eCl@ss	

### Global Properties

Product name	Schutzgehäuse IP69K
Materials	
- Material of the housings	Polycarbonate
-	PA6
Weight SLC/SLG	1.8 ... 2.3 kg

### Mechanical data

Design of electrical connection	cable gland fixed integrated
- Wiring of the transmitter	connector plug M12, 4-pole
- Wiring of the receiver	connector plug M12, 8-pole
Cable length	10 m

### Ambient conditions

Ambient temperature	
- Min. environmental temperature	-10 °C
- Max. environmental temperature	+50 °C
Storage and transport temperature	
- Min. Storage and transport temperature	-25 °C
- Max. Storage and transport temperature	+70 °C
Protection class	IP69K to IEC/EN 60529

## Dimensions

---

Dimensions	
- Durchmesser	50 mm
- Durchmesser End plugs	60 mm
- Height	500 ... 890 mm

## Documents

---

**Brochure** (it) 2 MB, 01.03.2018

Code: b\_optoshort\_it

**Brochure** (pt) 2 MB, 26.10.2018

Code: b\_optoshort\_pt

**Brochure** (es) 2 MB, 23.10.2018

Code: b\_optoshort\_es

**Brochure** (fr) 2 MB, 20.11.2018

Code: b\_optoshort\_fr

**Brochure** (en) 2 MB, 23.10.2018

Code: b\_optoshort\_en

**Brochure** (pl) 2 MB, 03.08.2018

Code: b\_optoshort\_pl

**Brochure** (de) 2 MB, 22.10.2018

Code: b\_optoshort\_de

## Images

---

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 13.02.2019 - 14:16:38h Kasbase 3.3.0.F.64I