

## Datasheet - SVM1/X-10/Y/E

Key transfer system / SVM1 - Key distribution station



(Minor differences between the printed image and the original product may exist!)

- Key-operated selector switch interlocking device with 10 keys





### Ordering details

Product type description	SVM1/X-10/Y/E
Article number	SVM1/X-10/Y/E
EAN Code	
notice	In the order/enquiry, the required key bitting numbers "X" (primary cylinder) and "Y" (secondary cylinder) must be indicated (e.g. SVM1/111-10/222/E)! If no lock number is indicated in the order/inquiry, we will supply a lock number at our discretion. The user must ensure that lock numbers are not assigned twice in a single plant (factory site)! The user must ensure that no double key bit numbers are allocated on one site (company site)!
eCl@ss	27-39-01-90

### Classification

Standards	EN ISO 13849-1
B10d Normally-closed contact (NC)	100.000
Mission time	20 Years
notice	$MTTF_d = \frac{B_{10d}}{0,1 \times n_{op}}$ $n_{op} = \frac{d_{op} \times h_{op} \times 3600 \text{ s/h}}{t_{cycle}}$

### Global Properties

Permanent light	Schlüssel-Verteilstation
Standards	EN ISO 13849-1, EN 1088
Compliance with the Directives (Y/N) 	Yes
Active principle	mechanical
Materials	
- Material of the housings	Stainless steel
- Locking bolt material	Brass
Housing coating	painted
- Enclosure color	 Silver
Color	
- Colour of the key grip	 Silver
- Colour of the key	 Silver
Weight	1930
Key number	
- primary key	X
- secondary key	Y
Locking system	Included in standard version
Key	10
Recommended combinations	SHGV, SVE
Front plate mounting (Y/N)	Yes

### Mechanical data

---

Mechanical life	100.000 operations
Switching frequency	5

### Ambient conditions

---

Ambient temperature	
- Min. environmental temperature	-25
- Max. environmental temperature	+50
Protection class	IP40 to IEC/EN 60529

### ATEX

---

Explosion protection categories for gases	None
Explosion protected category for dusts	None

### Dimensions

---

Dimensions	
- Width	120
- Height	52.5
- Length	240

### Included in delivery

---

SVM with 10 secondary key and 10 emergency keys, without primary key

### notice - Operating principle

---

see drawing	Primary key in Pos. 2: primary key not withdrawable, secondary key withdrawable Primary key in Pos. 1: primary key withdrawable, secondary key not
-------------	-------------------------------------------------------------------------------------------------------------------------------------------------------

## Ordering code

---

SVM1(1)(2)/(3)-(4)/(5)(6)/(7)

<b>notice</b>	<b>Not all variations can be supplied. The available order code used to convert the product part name.</b>
(1) without -Z/	Included in standard version Locking system Central locking system-Locking system
(2) without /SR	Included in standard version Silver coloured key heads
(3) X	Key number ( n) primary key 35 ... 99
(4) 6 10	6 secondary key 10 secondary key
(5) Y	Key number ( n) secondary key 100 ... 999
(6) oo/oo	Colour of the key grip  and all combinations resulting thereof
(7) E A	Mounting plate Assembly housing

## Documents

---

**Operating instructions and Declaration of conformity (da)** 2 MB, 25.09.2015

Code: mrl\_shgv-sve-svm\_da

**Operating instructions and Declaration of conformity (es)** 2 MB, 22.08.2016

Code: mrl\_shgv-sve-svm\_es

**Operating instructions and Declaration of conformity (jp)** 2 MB, 23.03.2017

Code: mrl\_shgv-sve-svm\_jp

**Operating instructions and Declaration of conformity (de)** 2 MB, 25.07.2016

Code: mrl\_shgv-sve-svm\_de

**Operating instructions and Declaration of conformity (fr)** 2 MB, 16.09.2016

Code: mrl\_shgv-sve-svm\_fr

**Operating instructions and Declaration of conformity (nl)** 2 MB, 08.08.2018

Code: mrl\_shgv-sve-svm\_nl

**Operating instructions and Declaration of conformity** (en) 2 MB, 25.07.2016

Code: mrl\_shgv-sve-svm\_en

**Operating instructions and Declaration of conformity** (pt) 2 MB, 23.08.2016

Code: mrl\_shgv-sve-svm\_pt

**Operating instructions and Declaration of conformity** (cn) 2 MB, 27.07.2017

Code: mrl\_shgv-sve-svm\_cn

**Operating instructions and Declaration of conformity** (pl) 2 MB, 22.11.2016



Code: mrl\_shgv-sve-svm\_pl


**Operating instructions and Declaration of conformity** (it) 2 MB, 02.09.2016

Code: mrl\_shgv-sve-svm\_it

## Images

---





Operating principle

---

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 13.02.2019 - 13:10:13h Kasbase 3.3.0.F.64l