

## Datasheet - SD-Y-POWER

Accessories SD interface / SD junction boxes M12



(Minor differences between the printed image and the original product may exist!)

- Accessories for series-wiring with serial diagnostics

### Ordering details

Product type description	SD-Y-POWER
Article number	103009361
EAN Code	
eCl@ss	27-27-24-91

### Global Properties

Permanent light	Power-Adapter für SD-Interface
Connector	1 x female connector, 8-pole 1 x male connector, 8-pole 1 x Connector, 4-pole
Design	Y-adapter
Weight	50
Recommended combinations	Solenoid interlock, Sensors
notice	Enables multiple entry points for the power supply of sensors and interlocks in SD installations.

For the supply voltage wiring, special M12 cables with a cable section of 4 x 0.75 mm<sup>2</sup> are used. The occurring voltage drop (due to the cable length, cable section) must be observed.

### Mechanical data

termination	M12
Bolting device	Screw locking

### Ambient conditions

Ambient temperature	
- Min. environmental temperature	-25
- Max. environmental temperature	+75

### Electrical data

Rated operating voltage	30
-------------------------	----

Operating current	4 A
Fuse rating for the operating voltage	4 A

## Dimensions

---

Dimensions	
- Width	38
- Height	20
- Length	54.5

## Documents

---

### **Mounting and wiring instructions** (de, en) 218 kB, 19.01.2018

Code: m\_sdyp01\_de-en

### **Brochure** (de) 6 MB, 15.02.2018

Code: b\_css\_brosch09\_de

### **Brochure** (en) 6 MB, 15.02.2018

Code: b\_css\_brosch09\_en

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 13.02.2019 - 12:38:48h Kasbase 3.3.0.F.64I