

Datasheet - RL



Command and signalling devices / Contact and light terminal blocks (RF/RL) System / Light terminal blocks (as voltage supply) with Ba9S holder / Light terminal block RL



- Print with incandescent lamp symbol

(Minor differences between the printed image and the original product may exist!)

Ordering details

Product type description	RL
Article number	101190088
EAN Code	
eCl@ss	27-37-13-02

Global Properties

Permanent light	Leuchtelement EL
Standards	IEC/EN 60947-1, EN 60947-5-1
Compliance with the Directives (Y/N)	No
Mounting	bayonet
Terminal designations	X1-X2
Mounting position	arbitrarily
Materials	
- Material of the housings	Plastic, glass-fibre reinforced thermoplastic self-extinguishing
Weight	20

Mechanical data

Connection type	Screw connection
Cable section	
- Min. Cable section	0,5, rigid 0,5, flexible
- Max. Cable section	2.5, rigid 1.5, flexible
Tightening torque for the terminals	1
Fitting design	Ba9S
Mounting flange position	3

mounting

pluggable

Ambient conditions

Ambient temperature

- Min. environmental temperature -25
- Max. environmental temperature +75

Protection class

- Protection class-Terminals IP20

Electrical data

Rated operating voltage 250

LED switching conditions display

With integrated LED (Y/N) No

Dimensions

Dimensions

- Width 10
- Length 46
- Depth 45

Documents

Mounting and wiring instructions (jp) 1 MB, 23.08.2012

Code: m_rdt01_jp

Mounting and wiring instructions (es) 1 MB, 23.08.2012

Code: m_rdt01_es

Mounting and wiring instructions (de) 1 MB, 01.12.2011

Code: m_rdt01_de

Mounting and wiring instructions (en) 1 MB, 01.12.2011

Code: m_rdt01_en

Images

K.A. Schmersal GmbH & Co. KG, Mödinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 13.02.2019 - 12:48:02h Kasbase 3.3.0.F.64I