# Datasheet - KG411-C

Command and signalling devices / Assembly housing KG / KG





(Minor differences between the printed image and the original product may exist!)

### **Ordering details**

Product type description KG411-C
Article number 101008567
EAN Code

eCl@ss 27-37-12-05

# **Global Properties**

Permanent light KG - Leergehäuse

Number of command positions 1

Materials

- Material of the housings ABS

- Housing color of upper part

- color of base part Grey

Color

Weight 140

#### **Mechanical data**

Cable entry M20 1

Knockout holes for cable gland (Y/N) No

Position of the cable gland bottom

### **Ambient conditions**

Ambient temperature

Min. environmental temperature
 Max. environmental temperature
 +65
 Protection class
 IP65

### **Dimensions**

### Dimensions

- Width 82

- Height 85

- Depth 80

Diameter of the through-holes for cable glands 22.3 + 0,4

Center-to-center distance of the drilled holes for the command posts 40

# Included in delivery

notice

Cable glands are not included in the delivery of the enclosure

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal The data and values have been checked throroughly. Technical modifications and errors excepted. Generiert am 13.02.2019 - 12:46:34h Kasbase 3.3.0.F.64I