

Datasheet - SEP 09.0.3.0.22/95

Two-hand control panels / SEP 09.0



(Minor differences between the printed image and the original product may exist!)

- Aluminium enclosure
- with removable aluminium cover at the bottom
- for separate mounting of the actuators for the two-hand control
- 2 black operating buttons (positioning parts) Ø 42 mm

Ordering details


Product type description	SEP 09.0.3.0.22/95
Article number	101022851
EAN Code	4250116203253
eCl@ss	27-37-12-19

Approval

Approval



Global Properties

Permanent light	SEP 09.0
Standards	IEC/EN 60947-5-5, EN ISO 13850, EN 574
Compliance with the Directives (Y/N) 	Yes
Number of operating push buttons (positioning parts)	2
- consisting of	EDP42SW; EF10.1; EF03.1
Materials	
- Material of the housings	Aluminium
- Material of the sealing plate	Aluminium
Housing coating	powder-coated
Colouring	
- Enclosure color	RAL 7004
Weight	3500
Suitable for EMERGENCY-OFF (Y/N)	No
Foot (Y/N)	No
Pre-wiring on terminal block (Y/N)	No
Stepped switching (Y/N)	No
Switching block (Y/N)	No
Construction kit possible (Y/N)	Yes
Recommended combinations	SRB201ZH, SRB200ZHX1, SRB201ZHX3

Mechanical data

Connection type	Screw connection
Cable section	
- Min. Cable section	
- Max. Cable section	1.5
Mechanical life	10.000.000 operations

Ambient conditions

Protection class	IP54
------------------	------

Electrical data

Number of shutters	2
Number of openers	2
Rated insulation voltage	440
Thermal test current	10 A
Utilisation category	AC-15: 250 V / 8 A DC-13: 24 V / 5 A

Dimensions

Dimensions	
- Width	155 (per enclosure)
- Height	160 (per enclosure)
- Depth	150 (per enclosure)
diameters for the actuating heads	
- Operating push buttons (positioning parts)	42

notice

Customer-specific executions (completely pre-wired, special paint, etc.)
The distance of the enclosure must be determined by the user to EN 574.
Optional: actuators with low actuating force
1 NO/1 NC contact per unit

Keywords

Two-hand control panels

Documents

Operating instructions and Declaration of conformity (pt) 1 MB, 06.04.2017

Code: mrl_sep_pt

Operating instructions and Declaration of conformity (es) 1 MB, 16.02.2017

Code: mrl_sep_es

Operating instructions and Declaration of conformity (cn) 2 MB, 23.11.2018

Code: mrl_sep_cn

Operating instructions and Declaration of conformity (it) 1 MB, 29.06.2017

Code: mrl_sep_it

Operating instructions and Declaration of conformity (de) 1 MB, 11.01.2017

Code: mrl_sep_de

Operating instructions and Declaration of conformity (fr) 1 MB, 01.03.2017

Code: mrl_sep_fr

Operating instructions and Declaration of conformity (nl) 1 MB, 13.08.2018

Code: mrl_sep_nl

Operating instructions and Declaration of conformity (pl) 1 MB, 16.02.2017

Code: mrl_sep_pl

Operating instructions and Declaration of conformity (en) 1 MB, 11.01.2017

Code: mrl_sep_en

EAC certification (ru) 779 kB, 05.10.2015

Code: q_6043p17_ru

Images

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 13.02.2019 - 14:53:56h Kasbase 3.3.0.F.64l