

## Datasheet - NDTGNOFL

Command and signalling devices / Push buttons and pilot lights - "N" Program / NDT - Push button



- Only for Position switch

(Minor differences between the printed image and the original product may exist!)

### Ordering details

|                          |             |
|--------------------------|-------------|
| Product type description | NDTGNOFL    |
| Article number           | 101184159   |
| EAN Code                 |             |
| eCl@ss                   | 27-37-12-13 |

### Approval

Approval



### Global Properties

|                                      |  |
|--------------------------------------|--|
| Permanent light                      | NDT - Push button                        |
| Standards                            | IEC/EN 60947-1, EN 60947-5-1             |
| Compliance with the Directives (Y/N) | Yes                                      |
| Suitable for safety functions (Y/N)  | No                                       |
| Mounting                             | mounting flange EFMH                     |
| Materials                            |  |
| - Material of the operators          | ABS                                      |
| - Material of the front ring         | ABS, Chromium-plated                     |
| Design                               | Embeddable button - Front plate mounting |
| Form                                 | Round                                    |
| Color                                |  |

|                                   |   |
|-----------------------------------|---|
| - Colour of the operating element | <input checked="" type="checkbox"/> green |
| - Colour of the bellows           | <input type="checkbox"/> White            |
| - Colour of the front ring        | <input type="checkbox"/> Silver           |
| Weight                            | 25  |
| Manner of using                   |   |
| Can be illuminated (Y/N)          | No  |

## Mechanical data

---

|                                     |         |
|-------------------------------------|---------|
| Actuating stroke                    | 5       |
| Latching (Y/N)                      | No      |
| Unlocking type                      | without |
| Probing possible (Y/N)              | Yes     |
| mounting flange available (Y/N)     | No      |
| Front plate thickness               |         |
| - min. front plate thickness        | 1.5     |
| - max. front plate thickness        | 6       |
| Tightening torque for fixing screws | 0,6     |

## Ambient conditions

---

|  |                    |
|--|--------------------|
| Ambient temperature                      |                    |
| - Min. environmental temperature         | -25                |
| - Max. environmental temperature         | +80                |
| Storage and transport temperature        |                    |
| - Min. Storage and transport temperature | -                  |
| - Max. Storage and transport temperature | -                  |
| Fully insulated (Y/N)                    | Yes                |
| Sealing type                             | membrane, lip seal |
| Protection type IP                       | IP67, IP69K        |

## LED switching conditions display

---

|                           |    |
|---------------------------|----|
| With integrated LED (Y/N) | No |
|---------------------------|----|

## Dimensions

---

|                                     |            |
|-------------------------------------|------------|
| Dimensions                          |            |
| - Height                            | 11 mm      |
| - diameters for the actuating heads | Ø 44.5     |
| - Hole, diameter                    | 22.3 + 0,4 |
| Spacing                             | 50 x 50    |

## Documents

---

**Operating instructions and Declaration of conformity (it)** 2 MB, 14.06.2017

Code: mrl\_programme-e-n-r\_it

**Operating instructions and Declaration of conformity (en)** 1 MB, 06.11.2018

Code: mrl\_programme-e-n-r\_en

**Operating instructions and Declaration of conformity (pl)** 2 MB, 12.10.2017

Code: mrl\_programme-e-n-r\_pl

**Operating instructions and Declaration of conformity** (jp) 2 MB, 28.06.2017

Code: mrl\_programme-e-n-r\_jp

**Operating instructions and Declaration of conformity** (pt) 2 MB, 31.05.2017

Code: mrl\_programme-e-n-r\_pt

**Operating instructions and Declaration of conformity** (de) 1 MB, 06.11.2018

Code: mrl\_programme-e-n-r\_de

**Operating instructions and Declaration of conformity** (es) 1 MB, 05.12.2018

Code: mrl\_programme-e-n-r\_es

**Operating instructions and Declaration of conformity** (nl) 1 MB, 05.12.2018

Code: mrl\_programme-e-n-r\_nl

**Operating instructions and Declaration of conformity** (fr) 1 MB, 05.12.2018

Code: mrl\_programme-e-n-r\_fr

**Operating instructions and Declaration of conformity** (cn) 2 MB, 21.06.2017

Code: mrl\_programme-e-n-r\_cn

**BG-test certificate** (de, en, fr) 174 kB, 31.07.2014

Code: z\_ndrp01

**IPA Data** (en) 248 kB, 09.11.2012



Code: i\_jpap02

**IPA Data** (de) 255 kB, 05.09.2014

Code: i\_jpap01

## Images

---



Application

---

## System components

---

## Product



#### **EFMH/SEK - mounting flange for Position switch**

- mounting flange with Position switch
- 30 mm x 42 mm x 92 mm
- Thermoplastic enclosure

---

#### **Accessories**



#### **101171324 - EFMH**



#### **NSK - Protective collar against unintentional contact**

- for pushbuttons and illuminated pushbuttons

---

#### **contact element**



#### **contact element EF - (N)**

- Flat plug-in connector
- Mounting flange position 2
- 21-22 (Contact labelling)

---

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 13.02.2019 - 12:53:58h Kasbase 3.3.0.F.64l