

Datasheet - KG422-A

Command and signalling devices / Assembly housing KG / KG



(Minor differences between the printed image and the original product may exist!)

Ordering details

Product type description	KG422-A
Article number	101008569
EAN Code	
eCl@ss	27-37-12-05

Global Properties

Permanent light	KG - Leergehäuse
Number of command positions	2
Materials	
- Material of the housings	ABS
- Housing color of upper part	■ Grey
- color of base part	■ Grey
Color	
Weight	190

Mechanical data

Cable entry M20	1
Knockout holes for cable gland (Y/N)	No
Position of the cable gland	above

Ambient conditions

Ambient temperature	
- Min. environmental temperature	-25
- Max. environmental temperature	+65
Protection class	IP65

Dimensions

Dimensions	
- Width	82
- Height	85

- Depth	80
Diameter of the through-holes for cable glands	22.3 + 0,4
Center-to-center distance of the drilled holes for the command posts	40

Included in delivery

notice

Cable glands are not included in the delivery of the enclosure

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 13.02.2019 - 12:46:35h Kasbase 3.3.0.F.64I