Datasheet - ELEK



Command and signalling devices / Contact and light terminal blocks (EF/EL) System / Light terminal blocks (as voltage supply) with Ba9S holder / Light terminal block EL





(Minor differences between the printed image and the original product may exist!)

Ordering details

Product type description ELEK
Article number 101167368

eCl@ss 27-37-13-02

Approval

Materials

EAN Code

Approval EAC

Global Properties

Permanent light Leuchtelement EL

Standards IEC/EN 60947-1, EN 60947-5-1

Compliance with the Directives (Y/N) $\mathbf{C}\mathbf{E}$

Terminal designations X1-X2
Mounting position arbitrarily

- Material of the housings Plastic, glass-fibre reinforced thermoplastic self-extinguishing

Weight 20 notice Print with LED symbol

Mechanical data

Connection type Cage clamps, WAGO Cage Clamp
Cable section

 $\begin{array}{lll} \text{- Min. Cable section} & 2 \times 0.08 \\ \text{- Max. Cable section} & 2 \times 1.5 \\ \text{Mounting flange position} & 3 \end{array}$

mounting pluggable

terminals Protection against polarity reversal

Ambient conditions

Ambient temperature

- Min. environmental temperature -25
- Max. environmental temperature +80

Protection class

- Protection class-Terminals IP20

Electrical data

Rated insulation voltage Ui 440 V
Rated operating voltage Ue 250 V

LED switching conditions display

With integrated LED (Y/N) No

LED switching conditions display

- Supply voltage UB 24 VAC/DC - colour of the LED without

Dimensions

Dimensions

 - Width
 10 mm

 - Length
 46 mm

 - Depth
 51 mm

Included in delivery

Illuminants have to be purchased optionally

Diagram



Note Diagram

opositive break NC contact

 $^{\scriptsize{\textcircled{\scriptsize{1}}}}$ active

no active

O—___O Normally-open contact

o----- Normally-closed contact

Documents

CCC certification (en) 1 MB, 20.06.2017

Code: q_efelp02


CCC certification (cn) 1 MB, 20.06.2017

Code: q_efelp03


EAC certification (ru) 779 kB, 05.10.2015

Code: q_6043p17_ru

Images



Application



K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal The data and values have been checked throroughly. Technical modifications and errors excepted. Generiert am 13.02.2019 - 12:47:28h Kasbase 3.3.0.F.64I