

Datasheet - STPLC-1

Two-hand control panels / Mounting post / STPLC - \$missingName\$




(Minor differences between the printed image and the original product may exist!)

- Welding construction with threaded holes for floor fixation
- without height adjustment
- without Spacer ring
- can be combined with operating panel SEP... to be used as two-hand foot-operated station

Ordering details

Product type description	STPLC-1
Article number	101024774
EAN Code	4250116203314
eCl@ss	27-37-12-81

Global Properties

Permanent light	STPLC - Ständer
Standards	EN ISO 13850, EN 574
Compliance with the Directives (Y/N) 	Yes
Materials	
- Material of the housings	Steel
Housing coating	powder-coated
Colouring	
- Enclosure color	RAL 7016
only with prime coating (Y/N)	No
Weight	15.000
with spacer ring (Y/N)	No
Height adjustable (Y/N)	No
suitable for foot switch mounting (with protective cover) (Y/N)	Yes
wheeled (Y/N)	No
Can be distinguished/recognised by scanner (Y/N)	No
ZPL plate with each time 1 x M32 x 1.5 and 2 x M25 x 1.5 outputs for	

cable glands (Y/N)	Yes
1 x M25 x 1.5 cable output at the stand pipe - inside of a removable flange cover; it seals a recess for a possible H-16 E plug-in connection (Y/N)	Yes
suitable for two-hand control of the type	SEPG 05.3, SEPK 02.0, SEP 01.0, SEP 01.4, SEP 07.0

Dimensions

Dimensions	
- Width	400
- Height	838
- Depth	400

Keywords

Support for Two-hand control panels

Images



Product photo