Datasheet - EDMSW



Command and signalling devices / Push buttons and pilot lights - "E" Program / ED - Push button



- with membrane
- Symbols still clearly visible under transparent membrane

(Minor differences between the printed image and the original product may exist!)

Ordering details

EDMSW Product type description Article number 101006268 EAN Code

27-37-12-12 eCl@ss

Approval

Approval



Global Properties

Permanent light ED - Push button

Standards IEC/EN 60947-1, EN 60947-5-1

Compliance with the Directives (Y/N) No Suitable for safety functions (Y/N) No

Mounting mounting flange Mounting position arbitrarily

Materials - Material of the operators Aluminium

- Material of the front ring Aluminium

Design Embeddable button - Front plate mounting Round

Form

Color

- Colour of the operating element
- Colour of the front ring

■ Black
Silver

Weight35Can be illuminated (Y/N)NoWith membrane (Y/N)Yesinflated edge (Y/N)No

Mechanical data

Mechanical life 10.000.000 operations

Switching frequency 1000

Actuating force 2

Actuating stroke 4

Latching (Y/N) No

Unlocking type without

Probing possible (Y/N) Yes

notice Unlocking by rotating the knurled button clockwise

mounting flange available (Y/N)

Yes

Front plate thickness

- min. front plate thickness 1
- max. front plate thickness 6
Tightening torque for fixing screws 0,6

Ambient conditions

Ambient temperature

Min. environmental temperature
 Max. environmental temperature

Storage and transport temperature

Min. Storage and transport temperature
 Max. Storage and transport temperature
 Fully insulated (Y/N)

Sealing type membrane, lip seal, Form seals

Protection type IP IP65

LED switching conditions display

With integrated LED (Y/N) No

Dimensions

Dimensions

 - Height
 14

 - Diameter total
 29.5

 - Diameter of the front ring
 Ø 29.5

 - Diameter of touch surface
 Ø 23

 Hole, diameter
 22.3 + 0,4

 Mounting hole
 22

 Spacing
 40 x 50

notice

Images

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal The data and values have been checked throroughly. Technical modifications and errors excepted. Generiert am 13.02.2019 - 12:48:11h Kasbase 3.3.0.F.64I