

Datasheet - STPSK-1

Two-hand control panels / Mounting post / STPSK - \$missingName\$




- mobile sheet metal bending construction with threaded holes for floor fixation
- with height adjustment
- with Spacer ring
- can be combined with operating panel SEP... and foot switches with protective shields to be used as two-hand foot-operated station

(Minor differences between the printed image and the original product may exist!)

Ordering details

Product type description	STPSK-1
Article number	101171474
EAN Code	4250116203291
eCl@ss	27-37-12-81

Global Properties

Permanent light	STPSK - Ständer
Standards	EN ISO 13850, EN 574
Compliance with the Directives (Y/N) 	Yes
Materials	
- Material of the housings	Steel
Housing coating	powder-coated
Colouring	
- Enclosure color	RAL 7016
only with prime coating (Y/N)	No
Weight	35000
with spacer ring (Y/N)	Yes
Height adjustable (Y/N)	Yes
suitable for foot switch mounting (with protective cover) (Y/N)	Yes
wheeled (Y/N)	Yes
Can be distinguished/recognised by scanner (Y/N)	Yes
ZPL plate with each time 1 x M32 x 1.5 and 2 x M25 x 1.5 outputs for	

cable glands (Y/N)

Yes

1 x M25 x 1.5 cable output at the stand pipe - inside of a removable flange cover; it seals a recess for a possible H-16 E plug-in connection (Y/N)

No

suitable for two-hand control of the type

SEPG 05.3, SEPK 02.0, SEP 01.0, SEP 01.4, SEP 07.0

Dimensions

Dimensions

- Width	500
- Height	740 ... 965
- Depth	520

Keywords

Support for Two-hand control panels

Images



Product photo



Product photo



Product photo

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal
The data and values have been checked thoroughly. Technical modifications and errors excepted.
Generiert am 13.02.2019 - 14:53:52h Kasbase 3.3.0.F.64I